

Precision balance KERN PCB



The standard in the laboratory



GLP/ISO record keeping of weighing data, balance adjustment etc. with date, time and identification no. in combination with an appropriate KERN printer. Ideal for monitoring and documenting your processes in accordance with your quality management system



Piece counting
Thanks to its high level of accuracy, it is ideal for counting very small parts



With the **recipe function** you can weigh the different ingredients of a mixture. For control purposes you can also call up the total weight of all the ingredients

Precision balance KERN PCB



Features

- **PRE-TARE function** for manual subtraction of a known container weight, useful for checking fill-levels
- **Freely programmable weighing unit**, e.g. display direct in special units such as length of thread g/m, paper weight g/m², or similar
- **Percentage determination**: makes it possible to store a given weight value (100 %) and to determine deviations from this target value
- **Ring-shaped draught shield** standard, only for models with weighing plate size **A**, weighing space ØxH 90x40 mm

Technical data

- Backlit LCD display, digit height 15 mm
- Weighing plate dimensions
 - A** Ø 81 mm
 - B** Ø 105 mm
 - C** WxD 130x130 mm
 - D** WxD 150x170 mm, see enlarged picture
- Weighing plate material
 - A** Plastic, with conductive lacquer
 - B, C, D** Stainless steel

- Optional battery operation, battery 9 V Block not standard. AUTO-OFF function to preserve the battery, can be switched off
- Overall dimensions (without draught shield) WxDxH 163x245x79 mm
- Permissible ambient temperature 5 °C / 35 °C

Accessories

- **Protective working cover** over keyboard and housing, standard, can be retrofitted, for models with weighing plate size
 - A** KERN PCB-A02
 - B** KERN PCB-A03
 - C** KERN PCB-A04
 - D** KERN PCB-A05
- **Hook for underfloor weighing** of hanging loads, standard, can be retrofitted, KERN 440-A01
- **Rechargeable battery pack internal**, can be retrofitted, operating time up to 48 h without backlight, charging time approx. 8 h. AUTO-OFF function to preserve the battery, can be switched off, KERN PCB-A01
- **Software Balance Connection**, for details see page 159, KERN SCD-4.0

- **Individual header data**: the free software KERN SHM-01 can be used to print 4 header lines on the printout for printers YKN-01, 911-013 and YKB-01N
- **RS-232/Ethernet adapter** to connect balances with an RS-232 interface to a network via Ethernet, for details see page 158, KERN YKI-01
- **Suitable test weights**, also with calibration certificate, see the internet
- **Suitable printers** see page 157 ff.

STANDARD











































OPTION



Model	Weighing range [Max] g	Readout [d] g	Reproducibility g	Linearity g	Min. piece weight [Counting] g/piece	Net weight approx. kg	Weighing plate	Option DAKKS Calibr. Certificate	
								DAKKS KERN	
KERN PCB 100-3	100	0,001	0,001	± 0,003	0,002	1,1	A	963-127	
PCB 250-3	250	0,001	0,001	± 0,005	0,002	1,1	A	963-127	
PCB 350-3	350	0,001	0,002	± 0,005	0,002	1,1	A	963-127	
PCB 200-2	200	0,01	0,01	± 0,02	0,02	1,1	B	963-127	
PCB 1000-2	1000	0,01	0,01	± 0,03	0,02	1,4	C	963-127	
PCB 2500-2	2500	0,01	0,01	± 0,5	0,02	1,4	C	963-127	
PCB 3500-2	3500	0,01	0,02	± 0,05	0,02	1,4	C	963-127	
PCB 1000-1	1000	0,1	0,1	± 0,2	0,2	1,4	C	963-127	
PCB 2000-1	2000	0,1	0,1	± 0,2	0,2	1,4	C	963-127	
PCB 6000-1	6000	0,1	0,1	± 0,3	0,2	2	D	963-128	
PCB 10000-1	10000	0,1	0,1	± 0,3	0,2	2	D	963-128	
PCB 6000-0	6000	1	1	± 2	2	2	D	963-128	

KERN Pictograms

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).	 Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).	 Suspended weighing: Load support with hook on the underside of the balance.
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 Battery operation: Ready for battery operation. The battery type is specified for each device.
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display. Additional convenient functions, such as barcode and back calculation functions.	 Rechargeable battery pack: Rechargeable set.
 Data interface RS-232: To connect the balance to a printer, PC or network.	 Totalising level A: The weights of similar items can be added together and the total can be printed out.	 Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.
 RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 Totalising level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display. Additional convenient functions, such as barcode and back calculation.	 Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
 USB data interface: To connect the balance to a printer, PC or other peripherals.	 Strain gauges: Electrical resistor on an elastic deforming body.	 Tuning fork principle: A resonating body is electromagnetically excited, causing it to oscillate.
 Bluetooth data interface: To transfer data from the balance to a printer, PC or other peripherals.	 Percentage determination: Determining the deviation in % from the target value (100 %).	 Electromagnetic force compensation: Coil inside a permanent magnet. For the most accurate weighings.
 WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.	 Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 Single cell technology: Advanced version of the force compensation principle with the highest level of precision.
 Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.	 Verification possible: The time required for verification is specified in the pictogram.
 Interface for second balance: For direct connection of a second balance.	 Vibration-free weighing: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.	 DAkkS calibration possible: The time required for DAkkS calibration is shown in days in the pictogram.
 Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram. For details see the glossary.	 Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.
 GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection.	 ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.	 Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.
 GLP/ISO log: With weight, date and time. Only with KERN printers, see "Accessories"	 Stainless steel: The balance is protected against corrosion.	 Warranty: The warranty period is shown in the pictogram.
 Piece counting: Reference quantities selectable. Display can be switched from piece to weight.		

Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2000 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

Your KERN specialist dealer:

Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkkS calibration of balances with a maximum load of up to 6 t
- DAkkS calibration of weights in the range of 1 mg - 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages D, GB, F, I, E, NL